

RENTAL PACKAGE

HK 3000GRTH Mobile Glycol Heating System

The HK 3000GRTH is designed for any contractor. Quiet, compact and efficient, yet powerful enough to thaw ground, cure concrete, or provide temporary heat for up to four new job sites at once.

TECHNICAL SPECIFICATIONS

Dimensions

| | |
|---------------------------------|-----------------|
| Length..... | 13' |
| Width..... | 6'6" |
| Height..... | 6'6" |
| Weight (Fuel Empty / Full)..... | 4700 / 6080 lbs |



FEATURES

Thaw up to 5,600 sq ft
 Cure up to 11,200 sq ft
 Temporary Heat up to 12,000 sq ft
 Computer Controlled System
 Digital Temperature Monitoring

Large Glycol Reservoir
 Large Access Doors
 Double Loop Technology
 Enclosed Electric Hose Reel
 CSA / UL Certified

Interior Lights
 Mud Tray
 Larger Wheels
 Flow Indicator
 Compressor

TECHNICAL DATA

| | |
|----------------------------|---|
| Hose | 4 - 700 ft field hoses; Unspool with one person |
| Supply Manifold | 4 - 5/8" & 1 - 1 1/4" quick connect |
| Return Manifold | 4 - 5/8" & 1 - 1 1/4" quick connect |
| Ground Thawing Capacity | 5,600 sq ft |
| Concrete Curing Capacity | 11,200 sq ft |
| Temporary Heating Capacity | 12,000 sq ft (Varies with R-Value) |
| Field Pump | 1 hp Centrifugal |
| Circulating Pump | 1/2 hp Centrifugal |
| Fuel Tank | 192 GAL |
| Run Time | Up to 120 Hours |
| Larger Wheels | Higher capacity & better towing |
| Flow Indicator | Ensures proper operation |
| Interior Lights | Standard for ease of night operation |
| Mud Tray | Added under the reel to catch mud debris |
| Heater Capacity | 273,000 BTUH heating fuel input |
| Glycol Tank | 96 GAL |
| Electrical Requirements | 2 - 120V AC 20A circuits |
| Generator | 1 - 7,000W |
| Axle | 1 - 7,000 lb Torsion Axle, Electric Brakes |
| Hitch | 2 5/16" (Pintle) |