



RENTAL PACKAGE INDIRECT FIRED HEATER

TECHNICAL SPECIFICATIONS

Model.....Indirect Fired Heater
 Dimensions
 Length.....95"
 Width.....32"
 Height.....54"
 Weight (approx).....1200 lb
 Fuel Type.....LP/NG

APPLICATIONS

- Job Site/Construction Heat
- General/Building Heat
- Temporary Shelter
- Industrial Heat
- Commercial/Institutional Heating

TECHNICAL DATA

Electrical Data	208 volt/13 Amps/3 Phase/60 Hertz
Blower	631,000 BTU/HR 5,000 CFM @ 2.0" Static Pressure 91% High Efficiency Heat Exchanger High Pressure In-Line Centrifugal Blower for Powerful Heat Distribution
Machine Control	Fan and Thermal Security Resettable from Control Box Full Humidity Proof Switch Box Central Control Panel and Pilot Lights for All Functions
General	CSA/AGA Certified Riello Industrial Burner Fuel Consumption: 6.5 Gal/Hr. LP or 6 Therms of NG 24" Supply and Return Outlet -- 100 Ft. max. of Duct Run Stainless Steel Construction to Withstand Harsh Environments Stackable Frame with Fork Pockets and Lifting Hooks Pull Preheated air through their recirculation flanges so the heater reaches temperature quicker, using less fuel.