

PRODUCT SPECIFICATIONS FOR 308 CR



ENGINE

Net Power	69.5 HP
Engine Model	Cat C3.3B
Stroke	4.7 in
Bore	3.7 in
Gross Power - SAE J1995	74.3 HP
Displacement	203 in ³
Rated Net Power - 2,200 rpm - U.S. EPA Tier 4 Final/EU Stage V - ISO 9249/EEC 80/1269	69.5 HP

WEIGHTS

Operating Weight	20077 lb
Note (1)	*Minimum Weight is based on rubber tracks, no counterweight, operator, full fuel tank, standard stick, blade and no bucket.
Note (2)	**Maximum Weight is based on steel tracks with rubber pads, counterweight, operator, full fuel tank, long stick, blade and no bucket.
Maximum Operating Weight with Cab**	20077 lb
Minimum Operating Weight with Cab*	18610 lb

WEIGHT INCREASE FROM MINIMUM CONFIGURATION

Steel Tracks with Pads	752 lb
Counterweight	552 lb

Long Stick

146 lb

TRAVEL SYSTEM

Maximum Traction Force - High Speed	6250 lb
Ground Pressure - Maximum Weight	5.8 psi
Ground Pressure - Minimum Weight	5.4 psi
Travel Speed - High	3.2 mile/h
Travel Speed - Low	1.9 mile/h
Maximum Traction Force - Low Speed	15175 lb
Gradeability - Maximum	30 degrees

SERVICE REFILL CAPACITIES

Fuel Tank	39 gal (US)
Hydraulic System	29 gal (US)
Hydraulic Tank	14 gal (US)
Cooling System	2.6 gal (US)
Engine Oil	3 gal (US)

HYDRAULIC SYSTEM

Digging Force - Bucket	13946 lb
Operating Pressure - Travel	4134 psi
Operating Pressure - Swing	3626 psi
Operating Pressure - Equipment	4134 psi

Digging Force - Stick - Long 8032 lb

Type Load Sensing Hydraulics with Variable Displacement Piston Pump

Note Flow and pressure are not combinable. Under load, as flow rises pressure goes down.

Pump Flow at 2,400 rpm 44 gal/min

Digging Force - Stick - Standard 9509 lb

Maximum Auxiliary Circuit - Primary - Pressure at Pump 4134 psi

Maximum Auxiliary Circuit - Secondary - Pressure at Pump 4134 psi

Maximum Auxiliary Circuit - Primary - Flow at Pump 35 gal/min

Maximum Auxiliary Circuit - Secondary - Flow at Pump 9 gal/min

SWING SYSTEM

Machine Swing Speed 10.6 r/min

Boom Swing - Right 50 degrees

Boom Swing - Left 60 degrees

BLADE

Height 17 in

Width - Standard 90.6 in

Width - Wide 96.5 in

CERTIFICATION - CAB

Top Guard	ISO 10262:1998 (Level I)
------------------	--------------------------

Roll Over Protective Structure (ROPS)	ISO 12117-2:2008
--	------------------

Tip Over Protective Structure (TOPS)	ISO 12117:1997
---	----------------

SOUND

Operator Sound Pressure (ISO 6396:2008)	72 dB(A)
--	----------

Note	European Union Directive "2000/14/EC"
-------------	---------------------------------------

Average Exterior Sound Pressure (ISO 6395:2008)	99 dB(A)
--	----------

DIMENSIONS - STANDARD STICK

Cab Height	100 in
-------------------	--------

Vertical Wall	117.8 in
----------------------	----------

Boom In Reach	120.4 in
----------------------	----------

Tail Swing with Counterweight	62.4 in
--------------------------------------	---------

Boom Swing - Right	36.8 in
---------------------------	---------

Track Belt/Shoe Width	17.7 in
------------------------------	---------

Maximum Reach	281.1 in
----------------------	----------

Stick Length	71.7 in
---------------------	---------

Maximum Blade Height	14.6 in
-----------------------------	---------

Boom Swing - Left	23.8 in
--------------------------	---------

Maximum Blade Depth	16 in
----------------------------	-------

O/A Track Width	90.6 in
------------------------	---------

Maximum Dig Height 265.2 in

Maximum Dump Clearance 187.4 in

Maximum Reach - Ground Level 273.6 in

Tail Swing without Counterweight 57.1 in

O/A Undercarriage Length 113.4 in

Swing Bearing - Height 29.7 in

Ground Clearance 13.8 in

Dig Depth 161.7 in

Note *Boom Height when stick is pinned in transport position with no attachments.

Overall Shipping Length - with Counterweight 264 in

Note (1) **Boom Height when stick is pinned in working position with attachments. Standard Stick offers only one pin position.

Overall Shipping Length - without Counterweight 258.8 in

Note (2) ***With blade positioned at the rear of the machine.

Height - Boom Working - With Tools** 104.7 in

Height - Boom Transport - No Tools* 95.7 in

DIMENSIONS - LONG STICK

Dig Depth 182.8 in

Boom Swing - Left	23.8 in
Maximum Dig Height	277.1 in
Maximum Blade Height	14.6 in
Track Belt/Shoe Width	17.7 in
Cab Height	100 in
Tail Swing with Counterweight	62.4 in
O/A Undercarriage Length	113.4 in
Maximum Dump Clearance	199.7 in
Boom Swing - Right	36.8 in
Maximum Blade Depth	16 in
Ground Clearance	13.8 in
Stick Length	92.8 in
Maximum Reach	300.7 in
Maximum Reach - Ground Level	293.7 in
Boom In Reach	126.6 in
Swing Bearing - Height	29.7 in
O/A Track Width	90.6 in
Tail Swing without Counterweight	57.1 in
Vertical Wall	134 in

Note *Boom Height when stick is pinned in transport position with no attachments.

Note (2) ***With blade positioned at the rear of the machine.

Note (1) **Boom Height when stick is pinned in working position with attachments. Standard Stick offers only one pin position.

Height - Boom Transport - No Tools* 89 in

Height - Boom Working - With Tools** 120.1 in

Overall Shipping Length - without Counterweight 6872 mm (270.6 in)***

Overall Shipping Length - with Counterweight 6872 mm (270.6 in)***

AIR CONDITIONING SYSTEM

Air Conditioning The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1 kg of refrigerant which has a CO2 equivalent of 1.430 metric tonnes.

SUSTAINABILITY

Recyclability 96%

308 CR STANDARD EQUIPMENT

ENGINE

Cat C3.3B Diesel Engine (U.S. EPA Tier 4 Final/EU Stage V) – Electronic Engine, Turbo, Diesel Particulate Filter (DPF)

Automatic Engine Idle

Automatic Engine Shutdown

Automatic Swing Brake

Automatic Two Speed Travel

Fuel Water Separator with Indicator

Radial Seal – Double Element Air Filter

Extended Life Coolant, -37° C (-35° F)

HYDRAULICS

Electronic Variable Displacement Piston Pump

Load Sensing/Flow Sharing Hydraulics

Power On Demand

Hydraulic Temperature Monitoring

Certified Accumulator

HYDO Advanced Hydraulic Oil

OPERATOR ENVIRONMENT

Top Guard ISO 10262 1998 Level I

ROPS ISO 12117-2:2008

Stick Steer Mode

Travel Cruise Control

Control Pattern Changer

Adjustable Wrist Rests

Molded Footrests

Removable, Washable Floor Mat

Travel Pedals and Hand Levers

Cat Key with Passcode Option

HVAC with Automatic Temperature Control

Hydraulic Lockout Controls

Integrated Lower Front Window

Assisted Front Window Overhead Storage

Rear Window Emergency Exit

Fabric, High Back, Suspension Seat

Retractable Seat Belt (75 mm/3 in)

Coat Hook

Cup Holder

LED Interior Light

Literature Holder

Mounting Bosses for Top and Front Guards

12V Power Socket

Radio – Bluetooth, Auxiliary, Microphone, USB (charging only)

Skylight

Signaling/Warning Horn

Cab and (left side) Boom Work Lights

Utility Space for Mobile Phone

Next Generation Color LCD Monitor (IP66)

– Jog Dial Interface

– Fuel Level and Coolant Temperature Gauges

– Maintenance and Machine Monitoring

– Performance and Machine Adjustments

– Numeric Security Code

– Multiple Languages

– Camera Ready (IP68 & IP69K)

– Hour Meter with Wake Up Switch

UNDERCARRIAGE

Greased and Lubricated Track
Tie Down Eyes on Track Frame
Dozer Blade
Dozer Float
Bolt-on, Reversible Wear Edge

BOOM, STICK AND LINKAGES

One Piece Boom (3400 mm/133.9 in)
Standard Stick (1820 mm/71.7 in)
Front Shovel Capable – Pin-on/Manual Coupler/Hydraulic Coupler (not available in all regions)
Thumb Ready (not available in all regions)

ELECTRICAL

12 Volt Electrical System
60 Ampere Alternator
Circuit Breaker
900 CCA Maintenance Free Battery
Battery Disconnect
Ignition Key Stop Switch

OTHER

Locks on External Enclosure Doors
Lockable Fuel Cap
Beacon Socket
Rear Reflectors

308 CR OPTIONAL EQUIPMENT

OPERATOR ENVIRONMENT

Push to Start with Bluetooth® Key
Air Suspension Heated Seat
Rain Visor
Next Generation Advanced Monitor (below are all included with Next Generation Advanced Monitor option)
– Touch Screen
– Site Reference System
– High Definition Camera Capable (IP68 & IP69K)
– Numeric Security Code

UNDERCARRIAGE

Wide Dozer Blade
Steel Tracks (450 mm/17.7 in wide)
Wide Steel Tracks (600 mm/23.6 in)

Steel Track with Rubber Pads
Track Guides

BOOM, STICK AND LINKAGES

Long Stick (2360 mm/92.9 in)
Attachments including Buckets, Augers and Hammers
2nd Auxiliary Hydraulic Lines
Boom Lowering Check Valve
Stick Lowering Check Valve
Certified Lifting Eye

ELECTRICAL

Product Link™ Elite (regulations apply)
Travel Alarm
Rearview Camera
Rotating Beacon

GUARDING

Mesh Front Guard ISO 10262 1998 Level I
Heavy Duty Front Guard ISO 10262 1998 Level II
Overhead Cab Guard ISO 10262 1998 Level II
Polycarbonate Front Window EN356 P5A
Track Guards

OTHER

Additional Counterweight
Water Jacket Heater
Refueling Pump
Variable Angle Boom (refer to 308 CR VAB brochure for VAB specs and additional information)