



## RENTAL PACKAGE

### 50/75 Ton Air Handler

Air handlers provide conditioned air for buildings, warehouses and industrial applications. Units are plumbed into a chilled water system for operation. Supply and return air panels can be configured on the sides or ends for application needs. Capable of operating on return air or 100% outside air with optimum performance. Vari drive control allows for varied airflow depending on the application.

#### SPECIFICATIONS:

Model.....50/75 Ton Air Handler  
 Dimensions  
 Length.....144"  
 Width.....82"  
 Height.....70"  
 Weight.....3,900 lbs

#### APPLICATIONS:

- Climate Control
- Comfort Heating
- Temporary Cooling
- Moisture Removal

#### TECHNICAL DATA:

<b>Design Cooling Data</b> Air Temps Chilled Water BTU's	13,500 SCFM Vari Drive Control for 5,000 - 13,500 SCFM 95° DB / 78° WB Entering 53° DB / 52° WB Leavng 120 GPM at 45° Entering 603.4 MBH at 80° DB/68° WB 949.7 MBH at 95° DB/78° WB
<b>Ductwork Configuration</b> Supply Air Return Air	4 x 20" Connections - 2 per panel 4 x 20" Connections - 2 per panel Panels are interchangeable on sides or ends
<b>Electrical Data</b> Volts/Ph/Hz	460 / 3/ 60 22 FLA
<b>Connections</b> Air Side Water Side	20" Flexible ductwork 4" Victaulic