DEHUMIDIFICATION UNIT





RENTAL PACKAGE

5000 DH Desiccant Dehumidifier

PRODUCT FEATURES:

- Operator Interface with Touch Screen Control:
 - 1. Monitor Temperature
- 2. Monitor Airflow
- 3. Make Adjustments Per Customer Requirements
- Process fan VFD Control Manually Adjustable
- Reactivation Fan VFD Control Automatic
- Reactivation Air Temperature and Fan Speed controlled through PLC to Maintain Maximum Performance
- Non-rusting Aluminum Construction
- Lightweight/Small Footprint
- User Friendly and Reliable Operation

TECHNICAL DATA:

APPLICATIONS:

- Mold/Fungus Prevention
- Surface Preparation and Coating
- Restoration Drying
- Corrosion PreventionElectronics Prevention
- Power Plant Lay-Up
- Power Plant Lay-Op
 Pharmaceutical
- Candy Manufacturing

Dehumidifier	Model Process Air Flow Reactivation Heat Source Total Static Pressure	5000 DH 5000 CFM 115 kW 8 inch WC
Dimensions	Length Width Height Weight	10' 5' 6' 2,100 lbs.
Electric	Volts Phases Hz FLA	480 3 60 180 Amps
General	Handling Connection Type Outlet Size Inlet Size	Four Way Fork Pockets & Overhead Lifting Cam-lock 19" 19"