

Product Specifications For 236D3



Engine

Gross Power - SAE J1995	74.3 HP
Net Power - SAE 1349	73.2 HP
Displacement	203 in ³
Stroke	4.7 in
Bore	3.7 in
Net Flywheel Power	73.2 HP
Engine Model	Cat 3.3B DIT (turbo)
Peak Torque - 1,500 rpm - SAE J1995	195 ft·lbf
Net Power - ISO 9249	73.9 HP

Operating Specifications

Rated Operating Capacity	1800 lb
Tipping Load	3600 lb
Breakout Force - Tilt Cylinder	5003 lb
Rated Operating Capacity with Optional Counterweight	2000 lb
Note	Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat 10 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Weights

Operating Weight	6567 lb
-------------------------	---------

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat 10 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Dimensions

Wheel Base	43.5 in
-------------------	---------

Height - Top of Cab	82 in
----------------------------	-------

Vehicle Width over Tires	66 in
---------------------------------	-------

Ground Clearance	7.7 in
-------------------------	--------

Departure Angle	26°
------------------------	-----

Maximum Dump Angle	48°
---------------------------	-----

Maximum Reach - With Arms Parallel to Ground	53.3 in
---	---------

Turning Radius from Center - Machine Rear	64.5 in
--	---------

Bucket Pin Height - Maximum Lift	122.9 in
---	----------

Length - Without Bucket	108.9 in
--------------------------------	----------

Rack Back Angle - Maximum Height	91°
---	-----

Turning Radius from Center - Bucket 83 in

Turning Radius from Center - Coupler 51.8 in

Clearance at Maximum Lift and Dump 92.9 in

Reach - Maximum Lift/Dump 16 in

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat 10 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Bumper Overhang - Behind Rear Axle 40.2 in

Maximum Overall Height 156.6 in

Length - With Bucket on Ground 137.3 in

Bucket Pin Height - Carry Position 7.5 in

Hydraulic System

Hydraulic Flow - Standard - Loader Hydraulic Flow 20 gal/min

Hydraulic Flow - High Flow - Maximum Loader Hydraulic Pressure 3335 psi

Hydraulic Flow - Standard - Hydraulic Power (Calculated) 39 HP

Hydraulic Flow - Standard - Loader Hydraulic Pressure 3335 psi

Hydraulic Flow - High Flow - Maximum Loader Hydraulic Flow 30 gal/min

Hydraulic Flow - High Flow - Hydraulic Power (Calculated)

58 HP

Cab

ROPS

ISO 3471:2008

FOPS

ISO 3449:2005 Level I

Power Train

Travel Speed - Forward or Reverse - Two Speed Option

10.6 mile/h

Travel Speed - Forward or Reverse - One Speed

7 mile/h

Service Refill Capacities

Chain Box - Each Side

2.3 gal (US)

Cooling System

3.7 gal (US)

Engine Crankcase

3 gal (US)

Fuel Tank

24.8 gal (US)

Hydraulic System

13.2 gal (US)

Hydraulic Tank

10.3 gal (US)

Noise Level

Outside Cab**

101 dB(A)

Note (2)

*The declared dynamic operator sound pressure levels per ISO 6396:2008. The measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.

Note (3)

**The labeled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC.

Inside Cab*

83 dB(A)

Note (1)

Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.

Air Conditioning System (If Equipped)

Air Conditioning

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.81 kg of refrigerant which has a CO2 equivalent of 1.158 metric tonnes.

236D3 Standard Equipment

ELECTRICAL

12 volt Electrical System

80 ampere Alternator

Ignition Key Start/Stop Switch

Lights: Gauge Backlighting, Two Rear Tail Lights, Two Adjustable Front and Rear Halogen Lights, Dome Light

Backup Alarm

Heavy Duty Battery, 850 CCA

OPERATOR ENVIRONMENT

Advanced Display with Rearview Camera: Full Color, 127 mm (5 in) LCD screen; Advanced Multi-operator Security System; On-screen Adjustments for Implement Response, Hystat Response and Creep Control

Gauges: Fuel Level, Hour Meter

Operator Warning System Indicators: Air Filter Restriction, Alternator Output, Armrest Raised/Operator Out of Seat, Engine Coolant Temperature, Engine Oil Pressure, Glow Plug Activation, Hydraulic Filter Restriction, Hydraulic Oil Temperature, Parking Brake Engaged, Engine Emission System

Adjustable Vinyl Seat

Fold In Ergonomic Contoured Armrest

Control Interlock System, when operator leaves seat or armrest raised: Hydraulic System Disables, Hydrostatic Transmission Disables, Parking Brake Engages

ROPS Cab, Open, Tilt Up

FOPS, Level I

Top and Rear Windows

Floor Mat

Interior Rearview Mirror

12 volt Electric Socket

Horn

Hand (Dial) Throttle, Electronic

Adjustable Joystick Controls

Anti-theft Security System with 6-button Keypad

Storage Compartment with Netting

POWER TRAIN

Cat C3.3B, Turbo Diesel Engine, Meeting Tier 4 Final and Stage V Emission Standards

Air Cleaner, Dual Element, Radial Seal

S-O-SSM Sampling Valve, Hydraulic Oil
Filters, Cartridge-type, Hydraulic
Filters, Canister-type, Fuel and Water Separator
Radiator/Hydraulic Oil Cooler (side-by-side)
Spring Applied, Hydraulically Released Parking Brakes
Hydrostatic Transmission
Four Wheel Chain Drive

OTHER

Engine Enclosure, Lockable
Extended Life Antifreeze, -36° C (-33° F)
Machine Tie Down Points (6)
Support, Lift Arm
Hydraulic Oil Level Sight Gauge
Radiator Coolant Level Sight Gauge
Radiator, Expansion Bottle
Cat ToughGuard™ Hose
Auxiliary, Hydraulics, Continuous Flow
Heavy Duty, Flat Faced Quick Disconnects with Integrated Pressure Release
Split D-Ring to Route Work Tool Hoses Along Side of Left Lift Arm
Electrical Outlet, Beacon
Belly Pan Cleanout
Variable Speed Demand Fan
Product Link™ PL240, Cellular

MANDATORY EQUIPMENT

Hydraulics, Standard or High Flow
Quick Coupler, Mechanical or Powered
Highly Visible Seat Belt, 50 mm (2 in) or 75 mm (3 in)
EU Preparation Package
Power Train: One Speed, One Speed with Speed Sensitive Ride Control, Two Speed or Two Speed with Speed Sensitive Ride Control
Tires, 10 × 16.5 or 12 × 16.5
PERFORMANCE PACKAGES:
- Performance Package H1: Standard Flow Hydraulics (No Self Level)
- Performance Package H2: Standard Flow Hydraulics, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)
- Performance Package H3: High Flow Hydraulics, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)
COMFORT PACKAGES:
- Open ROPS (C0): Static Seat (No Foot Throttle, Headliner, Heater or Door)
- Open ROPS (C1): Foot Throttle, Headliner, Cup Holder, and choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) (No Heater or Door)
- Enclosed ROPS with Heater (C2): Foot Throttle, Headliner, Heater and Defroster, Side Windows, Cup Holder, Radio Ready, choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) and Door (Glass or Polycarbonate)
- Enclosed ROPS with A/C (C3): C2 + Air Conditioner

236D3 Optional Equipment

OPTIONAL EQUIPMENT

Hand-Foot Style Controls

External Counterweights

Beacon, Rotating

Engine Block Heater - 120V

Oil, Hydraulic, Cold Operation

Paint, Custom

Product Link PL641, Cellular

Bluetooth® Radio with Microphone (AM/FM/Weather Band Receiver with USB and Auxiliary Input Jack)